

OIML and NTEP indicator XK3190-A12/A12E

Introduction:

Fast speed, high precision A/D conversion
 Anti-vibration software
 Applied in platform scale, floor scale, weighing system
 equipped with 1-4 load cell.



Features :~

- A/D conversion with readability 1/30000
- Use inner code to replace weight observing and analysis tolerance
- Software to strength anti-vibration ability
- Zero-tracking, Zero range setup (auto/manual)
- Setup digital filter intensity, range and stable time
- Counting function with unit data save protection in case of power off
- Alarm for low battery and auto power off when low battery

Optional function:

1. KG/LB switch function
2. Animal scale function (A12, A12S only)
3. Two fixed- value outputs function with TTL output

Specification :~

Model	A12E	
Input signal range	-10mV~15mV	
Input sensitivity	1V/e	
Load cell Excitation	Dc 5V:/150mA	
Max. load cell connection	4 at 350 ohm	
Display	6 bits LCD, 6 status indications	6 bits LED, 6 status indication
Optional interface	RS232C serial communication	
Transmission distance	RS232C30 meters	

* Designs and specifications are subject to change for improvement without prior notice.

BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: www.banhing.com

Email: enquiry@banhing.com