

Features:~

- Excellent general use bench or platform scale for shipping, receiving, checking, stock control, and much more
- Easy to set up and operate with stable, accurate, large display - plus, fully flexible internal software settings
- Compact & lightweight, AC adapter (standard) or battery operation - use it anywhere you need it, from warehouse to office
- Removable stainless steel weighing pan for easy cleaning
- Rugged heavy duty construction to take the punishment of industrial use, cleaning & transportation
- Optional RS-232C allows easy connection to a printer or computer for record keeping or system control. A current loop interface is also an available option
- Selection lb/kg via pushbutton
- Full scale pushbutton tare

Specifications:~

Model	FG-150KAL
Capacity	300lbs / 150kg
Readability	0.02lb / 0.01kg
Pan Size	15.4 x 20.9" / 390 x 530mm
Min. display	0.1lb / 2oz / 0.05lb
Number of samples	(can be changed to 10, 20, 50 or 100) pieces
Maximum counts	120,000 pcs
Minimum unit weight	1.25 g
Repeatability (Standard deviation)	0.02 kg
Linearity error	0.05 kg
Sensitivity drift	20 ppm/°C (10°C to 30°C / 50°F to 86°F)
Display	7 segment LCD display (Character height 26 mm)
Display update	10 times per second
Operating temperature	-10°C to 40°C / 14°F to 104°F, less than 85% RH (no condensation)
Power supply	AC adapter or C size (R14P / LR14) x 4 batteries
Battery operating	Approximately 150 hours with alkaline dry cell battery
Dimension (W x D x H)	15.35 x 30.35 x 30.75" / 390 x 771 x 781mm
Net Weight	36.2 lbs / 16.4 kg
Calibration weight (Factory setting)	300 lbs / 150 kg



* Designs and specifications are subject to change for improvement without prior notice.

BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: www.banhing.com

Email: enquiry@banhing.com