

Function:-

Designed to reach 100°C in 9 minutes. It is equipped with auto water filling, auto re-ignition and shut off of flame, flameout protection, low water level protection and pressure relief valve.

Stainless steel with well insulated wall to prevent burn. Patented burner to increase steaming speed and fuel efficiency.



STEAMING CAPACITY (KG/MIN)				
RICE	FLOUR	STEAK	FISH	CHICKEN
24/50	18/40	30/8	30/10	30/40
40/55	30/45	50/8	50/10	50/40
48/55	36/45	60/8	60/10	60/40
96/55	72/45	120/8	120/10	120/40

Specification :~

MODEL	DESCRIPTION		VOLTAGE (V)	POWER (KW)	INPUT STEAM PRESSURE	DIMENSION (CM)
	DOOR	POTS				
RS6	SINGLE	6	380	9	0.02Wpa	77 x 65 x 99
RS10		10		12		77 x 65 x 133
RS12		12				77 x 65 x 150
RS24	DOUBLE	24		12 + 12		154 x 65 x 150

* Designs and specifications are subject to change for improvement without prior notice.

BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: www.banhing.com

Email: enquiry@banhing.com