



# Features :~

# SÍMONA SÍMONA

#### **Excellent Quality:**

• Strictly in accordance with OIML R76, GB/T11883-2002 standards, and European CE directives.

## **High Safety:**

• Aluminum casting case, highly firm hook and ring, special load cell for safety installation.

## Strong Reliability:

• High quality components used on PCB for long time stability.

## **Broad Applicability:**

56mm high character display, 30m distance in sight, applicable in storage, textile, metallurgy industry, etc.

#### Simple Operation:

Automatic battery voltage checking, electricity saving, power off, and overloading alarm, with wireless remote controller, and dedicated charger, easy operation.

# Complete Function:

Equipped with dedicated infrared remote control device, available for kg/lb conversion, hold, tare, division option, stability regulation, accumulation/query, gross/net display, remote power off, etc.

# Specification :~

O I II A	SHIDTHE DINIVITE	
MODEL	OCS-Z	1
CAPACITY	20 TON x 10KG	
ACCURACY GRADE	OIML III	1
DISPLAY	56mm (2") LED	'n
THE SCOPE OF TARE	100% F.S.	
STABLE DISPLAY TIME	<10S	'n
OVERLOAD VALUE	Max Cap.+9e	
SAFE LOAD	125% F.S.	6
UTMOST LOAD	400% F.S.	1.1
CONTINUOUS USING TIME	≥8o hours	1
BATTERY (OCS-A/B/G)	6V/10Ah	
CHARGER	AC220V/DC9V1.5A	1
OPERATION TEMP.	$10^{0}$ C ~ + $40^{0}$ C	(N
OPERATION HUMIDITY	20ºC, ≤90% RH	
GROSS WEIGHT	23 kg	n.

# SIMO <u>Functions:~</u> ONA

✓ Zero, Tare and Hold

www.banhing.com

- ✓ Battery supervision
- ✓ Overload alarm/record
- Digital calibration; 3- point calibration
  - ✓ Resolution and unit switch
  - ✓ Gravity acceleration set

\* Designs and specifications are subject to change for improvement without prior notice.

# 萬興企業有限公司 **BAN HING HOLDING SDN BHD** No. 13-3 Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia Tel: +603 4048 1000 Fax:+603 4050 8000 WEB: www.simona.com.my Email: simona@banhing.com