

## **ELECTRIC CHAIN HOIST MODEL: HHBB SERIES**

Picc

www.banhing.com

KOID 

HHBB Series Electric Chain Hoist include suspension electric hoist, electric hoist with hand trolley, electric trolley with motor trolley and low headroom electric hoist. Every type could be equipped to single speed and double speed. Electric chain hoist has following features:

- Operating voltage is 24V/36V, safety to workers;
- Dual break system, immediately performed by automatic brake during emergency power cut;
- Limit switches to protect both lifting and dropping works to prevent from exceeding the limits;
- Special anti phase power protective device to control over failure circuit of wrong power connection.
- Hand switch us 4 push direction buttons with emergency button too.
- G80 galvanized or cementite lifting chain, high tensile alloy steel with heat treatment.
- Power 220V-660V, 50Hz/60Hz, 3 Phase; Dual voltage available.

## Specification :~

Single speed: Electric Chain Hoist with Hook, Electric Chain Hoist with Hand Trolley, Electric Chain Hoist with Electric Trolley 

							-	A.A			
Model	ННВВ										
	0.5-01s	01-01s	01-02s	1.5-01s	02-01s	02-02s	2.5-02s	03-01s	03-02s	03-03s	05-02s
Capacity	0.5	1	1	1.5	2	2	2.5	3	3	3	5
Lifting Speed (m/min)	7.2	6.8	3.6	8.8	6.6	3.4	5.6	5.6	4.4	2.2	2.8
Motor Power (kw)	1.1	1.5	1.1	3.0	3.0	3.0	3.0	3.0	3.0	1.5	3.0
Rotation Speed (r/min)	1440										
Travelling Speed (m/min)	12 Low Speed 11 m/min; High Speed 21 m/min										
Insulation Grade	F										
Power Supply	220V - 600V, 50HZ/60HZ, 3 PHASE; Daul Voltage Available										
Control Voltage	24V/36V/48V										
No. of Load Chain	1	1	2	1	1	2	1	1	2	3	2
Chain Dia (mm)	6.3	7.1	6.3	10	10	7.1	11.2	11.2	10	7.1	11.2
Net Weight (kg)	47	65	47	108	108	73	115	115	131	85	145
I-Beam (mm)	75-125	75-178	75-178	82-178	82-178	82-178	100-178	100-178	100- 178	100-178	112- 178

\* Designs and specifications are subject to change for improvement without prior notice.



司