

Digital Indicator

With Mini Printer

THE IDEAL INDICATOR

- Multi-function Indicator which can apply to: Checking Weighing, Truck Scale, and Simple Batching System.
- User Friendly Setup, Calibration and Operation Procedures
- Totally 15 different Printer Formats for Mini-Printer and Thermal Printer
- Programmable Computer and Printer Output Transmission and Data Format
- 5 Points Linear Correction System to prevent linear error from the load cell
- Built-in Digital Filter System to Prevent Environment Interference

FEATURE

- Password Function to Prevent Unauthorized Access
- Maximum Number of Load Cell = 8 x 350 ohm
- Up to 1/30000 Display Resolution
- 1,000,000 Internal Count
- Weighing Unit Selectable: Matrix and Avoirdupois
- Low Battery Warning Signal
- Built-in Backlight
- Built-in Rechargeable Battery
- Built-in RS-232 interface
- Bi-Direction Transfer between PC to Indicator with RS-232
- HI-LO-OK-ZERO 4 set points

SPECIFICATION

- Display: 6 digits LCD, 26mm height
- Display Resolution: Maximum of 30,000 counts
- Division: 1, 2, 5, 10, 20, 50 selection
- Input Sensitivity: 0.1uV / division or above
- Zero Adjustable Range: 2 mV ~ 20 mV
- Non-Linearity: +/- 0.0033% F.S.
- A/D Conversion Speed: 50 times / sec
- Maximum Input Voltage: 20 mV
- Load Cell Excitation: DC 5 V (up to 8 x 350Ω load cells)
- Zero Drift: 0.3 uV / °C (typ.)
- Span Drift: +/- 8 PPM / °C (typ.)
- Power supply: By built-in Rechargeable Battery and AC/DC Power Adaptor
- Operating Temperature: 0 ~ 40°C
- Operating Humidity: < 90 % R.H. Non-condensing
- Net Weight: 2.8 kg
- Dimension: 210 (D)X300 (W)X 130 (H)mm

OPTIONS AVAILABLE

- RELAY OUTPUT
- MINI-PRINTER
- UWE OP-5L REMOTE DISPLAY
- UWE OP-5S REMOTE DISPLAY
- PRINTER INTERFACE
- JUNCTION BOX FOR UP TO 8 LOAD CELL
- MOUNTING KIT



Mounting Kit (Option Item)

2009/03/03 13:01
P/No.
Ser. 1
N.W. 10.01 kg
Tare 4.19 kg
G.W. 14.20 kg

2009/03/03 13:02
P/No.123456
Ser. 2
N.W. 10.01 kg
Tare 4.19 kg
G.W. 14.20 kg

2009/03/03 13:02
P/No.123456
Total 2
TN.W. 20.02 kg
Tare 8.38 kg
TG.W. 28.40 kg

Print Out Sample

* Designs and specifications are subject to change for improvement without prior notice.

BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: www.banhang.com

Email: enquiry@banhang.com