

- ❖ Multi -function Indicator which can apply to: Checking Weighing, Truck Scale, and Simple Batching System.
- ❖ User Friendly Setup, Calibration and Operation Procedures.
- ❖ Totally 15 different Printer Formats for Mini-Printer and Thermal Printer
- ❖ Programmable Computer and Printer Output Transmission and Data Format
- ❖ 5 Points Linear Correction System to prevent linear error from the load cell
- ❖ Built-in Digital Filter System to Prevent Environment Interference

```

2009-02-03 13:01
P.No. 1
Ser. 1
N.W. 30.01 kg
Tare 4.13 kg
G.W. 34.29 kg

2009-02-03 13:02
P.No. 123456
Ser. 2
N.W. 10.01 kg
Tare 4.13 kg
G.W. 14.28 kg

2009-02-03 13:02
P.No. 123456
Total 2
T.N.W. 20.02 kg
Tare 8.38 kg
T.G.W. 28.40 kg
    
```

Print Out Sample

**Features:-**

- ❖ Password Function to Prevent Unauthorized Access
- ❖ Maximum Number of Load Cell = 8 x 350 ohm
- ❖ Up to 1/30,000 Display Resolution
- ❖ 1,000,000 Internal Count
- ❖ Weighing Unit Selectable: Matrix and Avoirdupois
- ❖ Low Battery Warning Signal
- ❖ Built-in Backlight
- ❖ Built-in Rechargeable Battery
- ❖ Built-in RS-232 interface
- ❖ Bi-Direction Transfer between PC to Indicator with RS-232
- ❖ HI-LO-OK-ZERO 4 set points



Mounting Kit (Option Item)



Digital Indicator

**Specification :-**

Model	<b>UWE22-600</b>
Capacity	600kg
Division	100g
Platform size	600 X 800 MM

\* Designs and specifications are subject to change for improvement without prior notice.