

### OIML and NTEP indicator XK3190-A12/A12E

#### Introduction:

Fast speed, high precision, A/D conversion

Anti-vibration software

Applied in platform scale, floor scale, weighing system equipped with 1-4 load cell.

- A/D conversion with readability 1/30000
- Use inner code to replace weight observing and analysis tolerance
- Software to strength anti-vibration ability
- Zero-tracking, Zero range setup (auto/manual)
- Setup digital filter intensity, range and stable time
- Counting function with unit data save protection in case of power off
- Alarm for low battery and auto power off when low battery

#### Optional function:

1. KG/LB switch function
2. Animal scale function (A12, A12S only)
3. Two fixed- value outputs function with TTL output

#### Specification : ~

| Model                 | A12E-CW (MS) series                           |       |       |       |
|-----------------------|-----------------------------------------------|-------|-------|-------|
| Capacity              | 60kg                                          | 150kg | 200kg | 300kg |
| Division              | 10g                                           | 20g   | 50g   |       |
| Platform Size         | 330(L) x 390(W) x 370(H) mm                   |       |       |       |
| Operation Temperature | 0°C ~ 40°C                                    |       |       |       |
| Power Supply          | AC Adaptor, 9V / 500 mA                       |       |       |       |
| Material              | Mild Steel Platform with Mild Steel Structure |       |       |       |

#### Specification : ~

| Model                 | A12E-CW (SS) series                                        |       |       |       |
|-----------------------|------------------------------------------------------------|-------|-------|-------|
| Capacity              | 60kg                                                       | 150kg | 200kg | 300kg |
| Division              | 10g                                                        | 20g   | 50g   |       |
| Platform Size         | 330(L) x 390(W) x 370(H) mm                                |       |       |       |
| Operation Temperature | 0°C ~ 40°C                                                 |       |       |       |
| Power Supply          | AC Adaptor, 9V / 500 mA                                    |       |       |       |
| Material              | Stainless Steel Platform with<br>Stainless Steel Structure |       |       |       |



\* Designs and specifications are subject to change for improvement without prior notice.

萬興企業有限公司  
**BAN HING HOLDING SDN BHD**

No. 13-3 Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia

Tel: +603 4048 1000

Fax: +603 4050 8000

WEB: www.banhing.com

Email: sales@banhing.com