

Features :~

Touch-key calibration

Automated calibration can be started by pressing keys. (ATX series)
Also, your external calibration weights can be used for span calibration (all models).

Easy setting - Best fit for weighing application

Quickly adjust the desired ratio of stability and response for every application, even during measurement, with one-touch operation.

Expanded Piece Counting function

Unit weights of up to 5 different samples can be easily entered, stored and recalled for use.

Comparator function

Compare samples to target values or pass/fail criteria; results are clearly indicated.

Formulation mode

Convenient for making many measurements of minute samples and seeking the total mass.

Windows Direct Communication Function

Send balance data to Excel® or other Windows® applications without installing any data communication software. By combining standard Auto Print functions with typical spreadsheet functions, even difficult applications can be easily automated. *RS232C interface is needed.



Specifications :~

Model	ATX 84	ATX 124	ATX 224	ATY 64	ATY 124	ATY 224
Capacity	82g	120g	220g	62g	120g	220g
Minimum Display	0.1mg					
Pan Size (mm) approx.	ø91					
Main Body Dimensions (mm) approx.	213(W) x 356 (D) x 338 (H)					
Weight (kg) approx.	6.2			6.0		
Power Requirement	12V, 1A					
Internal Calibration	Yes			No		

* Designs and specifications are subject to change for improvement without prior notice.

萬興企業有限公司
BAN HING HOLDING SDN BHD

No. 13-3 Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia
Tel: +603 4048 1000 Fax: +603 4050 8000
WEB: www.banhing.com Email: sales@banhing.com