



Epoxy coated shelves are hard strong and easy to clean. Tested - 35°C durability.



The arc angular design on the base plate complies with the requirements of sanitation requirement



Digital adjustable. Temperature control. Certified by CE & UL standard

- **Blower System**
- **Magnetic Solid Door**
- **Freezer** Normal Type: Suitable for meat storage
- Tested at ambient temperature of 38°C, with no load

- CW: Castor Wheel
- BF: Bullet Feet

### Specification :-

MODEL	SF2UPDC	SF2UPDF
NO. OF DOOR	2 DOOR	2 DOOR
SYSTEM	BLOWER	BLOWER
Temperature (Celsius)°C	-10 to -20	-10 to -20
External Dimension (mm)	660 x (760+30) x 2060	660 x (760+30) x 2060
Internal Dimension (mm)	540 x 640 x 1460	540 x 640 x 1460
Gross Volume (Liters)	505	505
Power	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz
Weight (kgs)	102	102
Compressor (HP)	1/2	1/2
Refrigerant / Grams	R404a / 520g	R404a / 520g
Defrost System	Defrost Heater	Defrost Heater
Temperature Control	Digital	Digital
Shelves (PVC)	4	4
Number of Clips	16	16
Unit for 20ft Container	23	23
Unit for 40ft Container	48	48

\* Designs and specifications are subject to change for improvement without prior notice.

萬興企業有限公司  
**BAN HING HOLDING SDN BHD**

No. 13-3 Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia  
Tel: +603 4048 1000 Fax: +603 4050 8000  
WEB: www.banhing.com Email: sales@banhing.com