

Features :~

- All Stainless Steel Housing and Platter
- Compact Size Low Profile Design
- Protection Devices against Overload and Shock
- 1/3000 and 1/15000 Resolution Versions are Available for Various Applications
- Bold Type LCD Display
- Simple and User Friendly Design
- Two Selectable Built-in Weight Units:- Metric and Avoirdupois
- Support Conversion between Metric and Avoirdupois Weight Units
- Equipped with Memory Accumulation, Memory Recall Automatic Tare, Power On Zero, Auto Zero Tracking, Full Subtractive Tare, Digital Auto Calibration and Auto Power Saving Function
- Low Battery Indicator
- Dual Power Source: By Built-in Rechargeable Battery or External Power Adaptor
- AC/DC Power Adaptor, Bubble Level and Adjustable feet Included



Specification :~

Model	MS 3000	MS-15K	MS-30K
Capacity	3000g	15kg	30kg
Division	0.1g	0.5g	1g
Platter (mm)	210 x 210mm all Stainless Steel		
Power Source	By Built-in Rechargeable Battery Or External Power Adaptor		
Operation Environment	0°C ~ 40°C (32°F ~ 104°F), Non-condensed, R.H <85%		
Net Weight	4.60 kg		

* Designs and specifications are subject to change for improvement without prior notice.

萬興企業有限公司
BAN HING HOLDING SDN BHD

No. 13-3 Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia
Tel: +603 4048 1000 Fax: +603 4050 8000
WEB: www.banhing.com Email: sales@banhing.com