

Features:~

- Bubble level, adjustable feet included
- Dual Power: By built-in rechargeable battery or external AC Power Adaptor (included)
- Rear display
- Backlight Display Type: 6 x 25mm Wide Angle LCD Display
- 24 Bit Delta-Sigma A/D Converter with 1,000,000 internal Counts
- Selectable Weighing Units (grams (1/60,000, 1/30,000 or 1/50,000 resolution), lb, lb-oz)
- All-in-one program includes: straight weighing function / counting function/ weight check function / quantity check function
- HI-OK-OL. Check status indicators
- Programmable HI-OK-OL Audio Output
- Equipped with power-on Zero tracking, digital motion filter at Zero & weighing, smart power-on-Zero, full tare range, Auto calibration functions
- Low battery indicator
- Charge status indicator

Optional:~

- RS-232 interface
- Relay output



Specification :~

Model No	Capacity	Division	Resolution
SEK-3000	3000g	0.05g	1/60000
SEK-6000	6000g	0.1g	
SEK-12K	12kg	0.2g	
SEK-30K	30kg	0.5g	
Power Source	By Built-in Rechargeable Battery or External Power Adaptor		
Max. Zero Range	2% of Rated capacity		
Max. Tare Range	100% of Rated capacity (Subtractive)		
Weight Units	Metric, Avoirdupois & Pieces		
Operation Environment	0° ~ 40°C (32° ~ 104°F), Non-condensed. R.H. <85%		

* Designs and specifications are subject to change for improvement without prior notice.

萬興企業有限公司
BAN HING HOLDING SDN BHD

No. 13-3 Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia
Tel: +603 4048 1000 Fax: +603 4050 8000
WEB: www.banhing.com Email: sales@banhing.com