

Poultry Scalding Machine

These models have the capacity of DE feathering 12-50 birds per process and 300 - 1200 birds per hour.

The materials used to construct the frame are Stainless Steel Angle and the body consists of stainless steel plate.



Specification :~

Model	Capacity	Size (L x W x H)	Power	S. Reducer	Material / Supply By
HPSM-8ES	6 ~ 8PCS	36 ½" x 26 ½" x 29" (Extra Small)	0.5HP (single phase)	50 1/50 (Taiwan)	Stainless Steel Automatic Regulated Hot Water
HPSM-12S	12PCS	41" x 27" x 29" (Small)		60 1/50 (Taiwan)	
HPSM-24M	24PCS	48" x 29" x 29" (Medium)	1HP (single phase)	60 1/50 (Taiwan)	
HPSM-50L	50PCS	66" x 29" x 34" (Large)	2HP (3 phase)	70 1/60 (Taiwan)	

* Designs and specifications are subject to change for improvement without prior notice.

BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: www.banhing.com

Email: enquiry@banhing.com