

## Shrink Tunnel Packing Machine

## **ABS Series**

Shrinking package machine adopts quartz far-infrared tube in direct heating shrinking Membrane achieve perfect contraction package. The machine is made reliable by electronic unlimited shift and booster in temperature control. The products packed can be sealed well, preventing from getting damp and against knocks. It is suitable for tight wrapping packaging of manypiece articles and tray package, which is applied in contraction package in food, beverage, candies, stationary, hardware tools, necessities and chemical products.



O pocopoconos i -	Speci	lication :-
-------------------	-------	-------------

Model	ABS-A400	ABS-B400	ABS-C450
Power Supply	220v 50 ~60Hz	220v 50~60Hz	380v 50~60Hz
Power	7.5KW	7.5KW	8.5KW
Conveyor Speed	0 ~ 10m/min	0 ~ 10m/min	0 ~ 10m/min
Conveyor Loading	5KG	5KG	5KG
Size of Shrink Oven	800 x 400 x 200	830 x 400 x 200	830 x 450 x 250
Machine size (mm)	1350 x 720 x 880	1350 x 790 x 880	1280 x 760 x 1360

<sup>\*</sup> Designs and specifications are subject to change for improvement without prior notice.

## BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia. Tel: 603-4048 1000 / 4042 5970 Fax: 603-4050 8000

Website: www.banhing.com

ig.com Email: enquiry@banhing.com