

## Closer Sewing Machine- Single Needle, Single Thread DA

- Trouble-free continuous operation: Closes bags at ease on the bagging line or in the field.
- Quiet operation: High-grade, wear-resistant nylon cam ensures minimum noise level in comparison to loud noise experienced in machines with steel cams during operation.
- Safety handle: Strong plastic handle for insulation.
- Non-corrosive finish: Essential as it helps resist corrosion in damp and humid conditions.
- Superior powerful lubricator: lubrication system consists of an oil pump direct the lubricant to the main moving parts.
- Sealed Motor: Ideal as it provides the motor with a total dust-proof enclosure.
- Automatic thread cutter: Protected cutting blades sever the thread after the bag is closed.
- Timing Belt: 15mm toothed belt helps the machine operate without much effort under tense workload.
- Adaptable: Stationary or suspended use can be attained from this machine without loss of useful portable features.
- Presser foot lifter and thread cone cover: Standard in all bag closing models.
- Optional accessories: Conveyor stands, shoulder belts, spring balancers with hangers are available at extra cost.

### STITCH SAMPLE



### Specifications: ~

Model	DA
Closing Speed	5-8 sec/bag fpm at 3.5 stitches/ inch(25.4mm)
Type of Stitch	Single thread/Chain Stitch
Stitch Length	3.5 stitches/inch (25.4mm) Fixed
Maximum material thickness	10mm
Cutter Type	Mechanical
Thread	8oz. Cotton or Synthetic thread cones
Needle Size	DB X 1 130/21 organ
Lubricant	For extended lubrication and wear, use SAE 30 Oil
Types of Bags	All kinds of multi-wall paper, Kraft-paper, burlap, cotton, PP/PE, Hessian, woven polyester, jute bags etc.
Dimension	30cm x 30cm x 33cm
Weight	6kg



## BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: [www.banhing.com](http://www.banhing.com)

Email: [enquiry@banhing.com](mailto:enquiry@banhing.com)