

## Protected against dust and water jets to IP65(EN60529)



Easy, effective and efficient! The 4 Series "basic" level is the ideal solution for applications in which simple weighing is key. Optimized for quick and easy weighing applications, six clearly-structured large format keys with tactile feedback combine with the easy-to-read 7-segment backlit LC display for clear and fast results on a device which couldn't be easier to use.

- Rugged industrial quality
- A single operating principle from milligrams to tons
- A variety of connection options: From serial interface to network
- A variety of applications: From simple weighing to multi-functional database application
- Min Weigh as standard, i.e. reliability for your weighing data
- Save time and money with ex-works-certified precision: Certified precision: Certified MonoBloc<sup>®</sup> scale with internal adjustment weight or certified scales with strain gauge weighing cells
- Available for mains or battery operation
- GMP-certified scale series
- Interface: 1 RS232(standard), additional RS232, RS485;USB, digital I/O interface options

Model	MBBA 425 series (LA)				
Capacity (kg)	3	6	15	35	60
Weighing Range ½ (kg)	1.5/3	3/6	6/15	15/35	30/60
Readability / Verification scale interval ½(g)	0.5/1	1/2	2/5	5/10	10/20
Max. readability (not certifiable) (g)	0.05	0.1	0.2	0.5	1
Repeatability (s) (g)	0.15	0.2	0.2	0.5	1
Linearity (s) (g)	+/-0.15	+/-0.2	+/-0.2	+/-0.5	+/-1
Stabilization time (s) (seconds)	-1.0				
Load plate (mm)	200 x 240		240 x 350		
Dimensions (mm)	265 x 335 x 100		360 x 370 x 115		

\* Designs and specifications are subject to change for improvement without prior notice.

## **BAN HING HOLDING SDN BHD**

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia. Tel: 603-4048 1000 / 4042 5970 Fax: 603-4050 8000 Website: www.banhing.com Email: enquiry@banhing.com