

SIMONA

Ready For You

Automatic Flow Packing Machine

- ❖ Double transducer control, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.
- ❖ Human-machine operation, convenient and quick parameter setting..
- ❖ Self diagnosis failure function, clear failure display..
- ❖ High sensitivity optical electric color mark tracking and digital input cut position which makes the sealing and cutting more accurate..
- ❖ Separate PID control to temperature, suitable for various packing materials..
- ❖ Stopping the machine in selected position, no sticking to the knife and no waste packing film..
- ❖ Simple driving system, reliable working, convenient maintenance..
- ❖ All the controls are achieved by software, convenient for function adjusting and upgrading.



www.banhing.com.my

Scope of application:

- Suitable for regular products like chocolate, moon cakes, biscuit, bread, candy, medicine, daily article, hard wares, tray etc.

PACKAGING FILM:

- OPP/PPP/PE etc.; must be used in roll, outer diameter ≤300mm, inner diameter is 75mm, the surface of the film must be unknit, no wave on the edge of the film, the color mark must evidently to the colour of the film.

Specification:~

MODEL	CT-320		
Type	EPM-2023		
Bag Size	(130-350)*(50-200)*(3-70)mm(L*W*H)		
Speed	25-180 bag/min		
Film Thickness	0.04-0.07MM		
Max Film Width	40MM		
Max Outer Diameter	300MM		
Power	Power Supply	220V-50Hz	
	Total Power	5.5KW	
Machine Size	Size	4000 x 950 x 1600 (lwh)	
	Weight	650KG	
Crate Size	Main Machine	1745(L) x 1100 (W) x 1610 (H) MM	
	Tail Machine	2560(L) x 370 (W) x 350 (H) MM	

*Designs and specifications are subject to change for improvement without prior notice.

萬興企業有限公司
BAN HING HOLDING SDN BHD

No. 13-3 Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia

Tel: +603 4048 1000

Fax: +603 4050 8000

WEB: www.simona.com.my

Email: simona@banhing.com