



Function:-

Designed to reach 100C in 9 minutes. It is equipped with auto water filling, auto re-ignition and shut off of flame, flameout protection, low water level protection and pressure relief valve.

Stainless steel with well insulated wall to prevent burn. Patented burner to increase steaming speed and fuel efficiency.

Specification :-

Description	Model	Gas	Input Steam Pressure (Pa)	Consume (kg/h)	Heat Load (MJ/h)	Steaming capacity (kg/min)					Dimensions (mm)
						Rice	Flour	Steak	Fish	Chicken	
Single door, 6 pots	GRS-6	LPG	2800	0.80	36.9	30/38	18/38	30/6	30/7	30/17	700x650x1130
Single door, 8 pots	GRS-8	LPG	2800	0.80	36.9	40/38	24/38	40/6	40/7	40/17	700x650x1300
Single door, 10 pots	GRS-10	LPG	2800	0.95	43.8	50/38	30/38	50/6	50/7	50/17	700x650x1470
Single door, 12 pots	GRS-12	LPG	2800	0.95	43.8	60/38	36/38	60/6	60/7	60/17	700x650x1640
Double doors, 24 pots	GRS-24	LPG	2800	0.95x2	43.8x2	120/38	72/38	120/6	120/7	120/17	1400x650x1640

* Designs and specifications are subject to change for improvement without prior notice.

BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: www.banhing.com

Email: enquiry@banhing.com