

Curved Glass Slanting Lid Freezer

Outer Panel & Interior cabinet

- Mild Steel and Galvanized steel Sheet with epoxy powder coating

Evaporator & Condenser

- Zink coated buddy tube

Insulation

- Polyurethane foam, 60mm thick (CFC free) 38mm thick for cooler

Refrigerant

- R 134a (CFC free)

Power Source

- 220-240V, single Phase



Specification :-

MODEL	SM250SC	SM350SC	SM450SC
EXTERNAL DIMENSION(mm)	W827 x D623 x H895 x H1(825)	W1052 x D662 x H895 x H1(825)	W1332 x D6695 x H895 x H1(825)
INTERNAL DIMENSION (mm)	W695 x D491 x H732 x H1(666)	W920 x D530 x H723 x H1(666)	W1200 x D563 x H723 x H1(666)
TOTAL CAPACITY	205L	300L	430L
EFFECTIVE CAPACITY	175L	255L	370L
LID/DOOR TYPE	Curved Glass Slanting Lid	Curved Glass Slanting Lid	Curved Glass Slanting Lid
POWER CONSUMPTION (24H AT 30°C AMBIENT)	2.8kWh	3.7kWh	3.9kWh
TEMP. RANGE AT 30°C AMBIENT	-18 C to -26 C	-18 C to -26 C	-18 C to -26 C
NET WEIGHT	48kg	59kg	71kg
GROSS WEIGHT	58kg	71kg	87kg
COMPRESSOR POWER	1/5hp	1/4hp	1/3hp

* Designs and specifications are subject to change for improvement without prior notice.

BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: www.banhing.com

Email: enquiry@banhing.com