

# Multi-Functional Gas Extracting Packaging Machine (Vacuum)

## Feature:~

DZQ-600L non chamber multi-functional gas extracting packaging machine not only can achieve the process of sealing, but also vacuum extraction or inert gas flushing after vacuum cycle.

Due to chamber less design with double gas nozzles, its application is not limited by the size of vacuum chamber. The machine is ideal for the applications that have low demand on vacuum degree but high demand on the purity of inert gases.

Model DZQ -600L /S with double heating system is ideal for sealing relatively thick plastic bag and compound bag. Special sealing lengths 700mm, 800mm and 1000 mm are available.

For the powder smaller than 100 meshes, the machine should be equipped with Helix Subside Filter for collecting powder in order to protect vacuum pump.



## Specification :~

Model	DZQ-600L(/S)
Voltage	AC 380V/50Hz or 220V/50Hz
Sealing Power	600W (1000W)
Motor Power	750W
Air Compressor	1100W
Seal Length	600mm (700mm 800mm 900mm 1000mm)
Seal Width	10mm
Distance from Sealing Center to Conveyor	1250mm
Pump Capacity	20m <sup>3</sup> /h
Film Thickness (Single Layer)	≤0.18mm
External Dimensions (L*W*H)	945*900*1900mm
Net Weight	255kg

\* Designs and specifications are subject to change for improvement without prior notice.

萬興企業有限公司  
**BAN HING HOLDING SDN BHD**

No. 13-3 Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia

Tel: +603 4048 1000

Fax: +603 4050 8000

WEB: www.simona.com.my

Email: simona@banhing.com