

Chest Freezer Flat Glass Slanting Lid

Cutex Panel & Interior Cabinet

Mild steel and galvanized steel sheet with epoxy powder coating

Evaporator & Condenser

Zink coated bundy tube

Insulation

Polyurethane foam, 60mm thick(CFC Free)
38mm thick for cooler

Refrigerant

R 134a (CFC Free)

Power Source

220-240v, single phase 50Hz



Specification :-

MODEL	450 GL	600 GL	750 GL
TOTAL CAPACITY	420L	540L	710L
EFFECTIVE CAPACITY	360L	460L	600L
EXTERNAL DIMENSION	1329W x 662D x 865H	1659W x 662D x 865H	2094W x 662D x 865H
INTERNAL DIMENSION	1200W x 530D x 703H	1530W x 530D x 703H	1966W x 530D x 703H
DOOR TYPE	FLAT GLASS SLIDING LID		
INPUT POWER	200W	220W	250W
POWER SOURCE	Single Phase 220V-240V 50Hz		
OPERATING CURRENT	1.8A	1.9A	2.5A
POWER CONSUMPTION (24h at 30°C ambient)	4kWh/24h	4.4kWh/24h	5.3kWh/24h
TEMPERATURE RANGE (at 30°C ambient)	≥ -18°C		
NET WEIGHT	75KG	87KG	112KG
GROSS WEIGHT	91KG	109KG	137KG
COMPRESSOR POWER	1/3	1/3	3/8
COLOR	WHITE		

* Designs and specifications are subject to change for improvement without prior notice.

BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: www.banhing.com

Email: enquiry@banhing.com