

Chest Freezer Lifting Door

Cuter Panel & Interior Cabinet

Mild steel and galvanized steel sheet with epoxy powder coating

Evaporator & Condenser

Zink coated Bundy tube

Insulation

Polyurethane foam, 60mm thick (Cyclopentene - CFC Free)
38mm thick for cooler

Refrigerant

R 134a (CFC Free)

Power Source

220-240v, single phase 50Hz



Specification :-

MODEL	150 LD	250 LD	350 LD	450 LD	600 LD/LDD	750 LDD
TOTAL CAPACITY	150L	230L	320L	420L	540L	710L
EFFECTIVE CAPACITY	137L	210L	290L	395L	505L	655L
EXTERNAL DIMENSION	610W x 705D x 865H	820W x 705D x 865H	1045W x 705D x 865H	1325W x 705D x 865H	1655W x 705D x 865H	2090W x 705D x 865H
INTERNAL DIMENSION	485W x 530D x 703H	695W x 530D x 703H	920W x 530D x 703H	1200W x 530D x 703H	1530W x 530D x 703H	1966W x 530D x 703H
DOOR TYPE	LIFTING SOLID DOOR					
INPUT POWER	100W	120W	140W	180W	210W	240W
POWER SOURCE	Single Phase 220V-240V 50Hz					
OPERATING CURRENT	1.0A	1.2A	1.4A	1.6A	1.8A	2.4A
POWER CONSUMPTION (24h at 30°C ambient)	2.0kWh/24h	2.6kWh/24h	2.7kWh/24h	3.0kWh/24h	4.0kWh/24h	5.1kWh/24h
TEMPERATURE RANGE (at 30°C ambient)	-18°C ~ -26°C					
NET WEIGHT	40KG	45KG	52KG	66KG	78KG	100KG
GROSS WEIGHT	48KG	55KG	64KG	82KG	100KG	125KG
COMPRESSOR POWER	1/8	1/6	1/5	1/4	1/3	3/8
COLOR	WHITE					

* Designs and specifications are subject to change for improvement without prior notice.

BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: www.banhing.com

Email: enquiry@banhing.com