

## Commercial Bottle Cooler

### Outer Panel & Interior Cabinet

Mild steel and galvanized steel sheet with epoxy powder coating

### Evaporator & Condenser

Zink coated bundy tube

### Insulation

Polyurethane foam, 60mm thick (CFC Free) 38mm thick for cooler

### Refrigerant

R 134a (CFC Free)

### Power Source

220-240v, single phase 50Hz



### Specification :-

MODEL	200 BC	300 BC
EXTERNAL DIMENSION(MM)	620(W) x 610(D) x 1420(H)	620(W) x 625(D) x 1780(H)
INTERNAL DIMENSION(MM)	524 x 460 x 1019	524 x 530 x 1300
TOTAL CAPACITY	250 Liters	365 Liters
EFFECTIVE CAPACITY	210 Liters	320 Liters
LID/DOOR TYPE	Heated / Tempered Glass Door	Heated / Tempered Glass Door
INPUT POWER	300W	360W
RATE INPUT POWER	580 W	
POWER CONSUMPTION	3.4 kWh/24h	4.9 kWh/24h
TEMPERATURE RANGE AT 30°C AMBIENT	0°C - 4°C	0°C - 4°C
NET WEIGHT	79 KG	87 KG
GROSS WEIGHT	83 KG	91 KG
COMPRESSER POWER	1/5 HP	1/4 HP
COLOR	WHITE	WHITE

\* Designs and specifications are subject to change for improvement without prior notice.

## BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: [www.banhing.com](http://www.banhing.com)

Email: [sales@banhing.com](mailto:sales@banhing.com)