

Chest Freezer Flat Glass Slanting Sliding Lid

Outer Panel & Interior Cabinet

Mild steel and galvanized steel sheet with epoxy powder coating

Evaporator & Condenser

Zink coated Bundy tube

Insulation

Polyurethane foam, 60mm thick
(Cyclopentene - CFC Free)
38mm thick for cooler

Refrigerant

R 134a (CFC Free)

Power Source

220-240v, single phase 50Hz



Specification :-

MODEL	250GTS	350GTS	450GTS
TOTAL CAPACITY	205L	300L	430L
EFFECTIVE CAPACITY	175L	255L	370L
EXTERNAL DIMENSION	827W x 623D x 895H x 825H1	1052W x 662D x 895H x 825H1	1332W x 695D x 895H x 825H1
INTERNAL DIMENSION	695W x 491D x 723H x 666H1	920W x 530D x 723H x 666H1	1200W x 563D x 723H x 666H1
DOOR TYPE	Slanting Flat Glass Lid		
INPUT POWER	150W	180W	190W
POWER SOURCE	Single Phase 220V-240V 50Hz		
OPERATING CURRENT	1.3A	1.6A	1.8A
POWER CONSUMPTION (24h at 30°C ambient)	2.8kWh/24h	3.7kWh/24h	3.9kWh/24h
TEMPERATURE RANGE (at 30°C ambient)	≥ -18°C		
NET WEIGHT	48KG	59KG	71KG
GROSS WEIGHT	58KG	71KG	87KG
COMPRESSOR POWER	1/5	1/4	1/3
COLOR	WHITE		

* Designs and specifications are subject to change for improvement without prior notice.

BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: www.banhing.com

Email: enquiry@banhing.com