

Feature :-

- Compact, light weight, mobility, low noise and pollution, less energy consumption, and easy installation. The machine outlet can be connected to any direction. Sieved material can be discharged straight away, suitable for automated operation.
- No blockage on screen, high efficiency, applicable for 400 mesh or finer.
- Unique screen design, quick for changing screens which takes only 3-5 minutes. Easy to clean.
- Easy operation and maintenance. It can be use for single deck or multi decks. All the surfaces touch with raw materials are make by stainless steel to ensure a hygienic operation.



Specification :-

Model	Capacity (kg/hr)	Motor (HP)	Voltage (V)	Frequency (HZ)	Speed (RPM)	Effective Diameter of Screen	Dimension (mm)			No. of Deck	Net Weight (kg)
							L	W	H		
GY-440-1S	120	3/4	380	50	1440	358mm	510	510	707	1	90
GY-440-2S							510	510	827	2	98
GY-440-3S							510	510	948	3	106
GY-600-1S	180	1	380	50	1440	525mm	600	600	853	1	105
GY-600-2S							600	600	986	2	150
GY-600-3S							600	600	1120	3	165
GY-800-1S	210	1	380	50	1440	730mm	800	800	854	1	200
GY-800-2S							800	800	987	2	225
GY-800-3S							800	800	1121	3	250
GY-1000-1S	300	2	380	50	1440	900mm	1000	1000	920	1	235
GY-1000-2S							1000	1000	1060	2	265
GY-1000-3S							1000	1000	1196	3	295
GY-1200-1S	350	2.5	380	50	1440	1100mm	1200	1200	1037	1	340
GY-1200-2S							1200	1200	1197	2	365
GY-1200-3S							1200	1200	1356	3	390
GY-1500-1S	500	3	380	50	1440	1400mm	1500	1500	1110	1	515
GY-1500-2S							1500	1500	1285	2	-
GY-1500-3S							1500	1500	1461	3	-

***Capacity is estimated based on applying mesh #60. Actual may vary from materials and other factors.

BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: www.banhing.com

Email: enquiry@banhing.com