

Features:~

- Multi-weighing units:
Kg, lb, N are selectable, generally kg is the default unit.
- Multi-function operation:
Tare, Zero, Auto zero tracking, Total, Hold, Overload warning, operation through remote controller functions.
- User-friendly design:
Cast aluminum housing for maximum protection: Large red 5 digit LED display (digit height 30mm); Battery Operated with low battery indication; Automatic turn off, power-saving function.





Accessories



Infrared remote control



Adaptor(DC9V/1000mA)



Specification :~

| Model | Capacity | Division | Dimension(mm) | Weight |
|----------------|----------|----------|--|--------|
| 14192-701E-2T | 2000kg | 1kg | 95(A)x260(B)x40(C)x195(D)x135(E)x430(H) | 11.5KG |
| 14192-701E-3T | 3000kg | 1kg | 95(A)x260(B)x40(C)x195(D)x135(E)x430(H) | 11.5KG |
| 14192-701E-5T | 5000kg | 2kg | 120(A)x325(B)x50(C)x240(D)x165(E)x535(H) | 17.5KG |
| 14192-701E-10T | 10000kg | 5kg | 124(A)x325(B)x60(C)x240(D)x165(E)x660(H) | 27.5KG |

* Designs and specifications are subject to change for improvement without prior notice.

BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4041 0000

www.banhing.com